

NORMALLY OPEN SOLENOID VALVE FOR GAS 6 BAR

AUTOMATIC – EVA-6 ND 15 TO 50

FEATURES

The EVA-6 solenoid valves are intended for ambient bleed of non-corrosive combustible gas up to 6 bar, they are open when unenergized (normally open) and closing when energized.

Can be mounted in any position except upside down.

AVAILABLE MODELS

BSPP threaded from 1/2" to 2"

DC Supply voltage: 12VDC* - 24VDC

AC Supply voltage: 12V/50Hz* - 24V/50 Hz - 110V 50/60 Hz - 230V 50/60 Hz

*Except ND > 25

OPTIONAL FEATURES

CPI closed position switch (factory mounted)

OPI open position switch (factory mounted)

1/4" pressure connections

NPT threaded connections

LIMITS OF USE

	ND 15 to 50
Pressure rating PS	6 bar
Ambient temperature TS	-20°C / +60°C
Fluid temperature TS	-20°C / +60°C



WET PARTS

ND	15 - 50
Body	Aluminium EN AB 46100
Cover & bottom	Aluminium EN AB 46100
Shutter	Aluminium 11S
Sealings	NBR

DIRECTIVES AND MANUFACTURING STANDARDS

Subject	Standard	Subject	Standard
Gas regulation UE	EN 16304 / EN 16311	PED directive	2014/68/UE
Threaded connections	EN 10226	EMC directive	2014/30/UE
ROHS II directive	2011/65/UE	LVD directive	2014/35/UE

SOLENOID AND OPTIONAL CPI SWITCH PROTECTION

Protection rating	IP 65
--------------------------	-------

Power connection for ND15 to ND50 is through a dedicated DIN T30 connector with a built-in current rectifier for the alternative voltages and with an M20 cable gland.

Information given as an indication only, and subject to possible modifications



SECTORIEL S.A.
45 rue du Ruisseau
38290 SAINT QUENTIN-FALLAVIER – FRANCE
Tél: +33 4 74 94 90 70 - Fax: +33 4 74 94 13 95
www.sectoriel.com / Email: sectoriel@sectoriel.fr

Pages	1/4
Ref.	TDS9265M
Rev.	04
Date	09/2025

NORMALLY OPEN SOLENOID VALVE FOR GAS 6 BAR

AUTOMATIC – EVA-6 ND 15 TO 50

ELECTRICAL SPECIFICATIONS


Ø	Voltage	Solenoid code	Connector code	Absorbed power at peak	Absorbed power at full speed
1/2" - 3/4" - 1" ND 15 - ND 20 - ND 25	12V DC	BO-0510	CN-2100	23 VA	6 VA
	12V 50Hz	BO-0510	CN-2110	20 VA	6 VA
	24V DC	BO-0520	CN-2100	27 VA	7 VA
	24V 50Hz	BO-0520	CN-2110	24 VA	7 VA
	110V 50/60 Hz	BO-0530	CN-2120	29 VA	9 VA
	230V 50/60 Hz	BO-0540	CN-2130	30 VA	9 VA
1 1/4" - 1 1/2" - 2" ND 32 - 40 - 50	24V DC	BO-0355	CN-2100	68 VA	18 VA
	24V 50Hz	BO-0355	CN-2110	68 VA	18 VA
	110V 50/60 Hz	BO-0365	CN-2120	77 VA	23 VA
	230V 50/60 Hz	BO-0375	CN-2130	89 VA	25 VA

OPTIONAL CPI/OPI SWITCHES SPECIFICATIONS

Ambien temperature TS	-20 / +60°C
Switchable voltage	1000V DC or AC peak
Switchable current	1A (DC or AC peak)
Switchable power	Max 40W
Resistance	200 mΩ

The CPI/OPI limit switches are of the SPST NO magnetic proximity sensor type (open at rest).
Connection by DIN connector.

INSTALLATION EXAMPLE



N°	Item	N°	Item
1	FM gas filter	8	EVA-6 Automatic discharge solenoid valve
2	OPSO: Over Pressure Self Operating device	9	Outside reset
3	RG/2MC pressure regulator	10	Burner control
4	Minimum pressure switch	11	MTC10 leak test device
5	EVP/NC fast opening automatic solenoid valve	12	MVS/1 relief valve
6	Maximum pressure switch	13	Pressure gauge with relative button
7	EVPT slow opening automatic solenoid valve	14	Gas detector

Information given as an indication only, and subject to possible modifications



	SECTORIEL S.A. 45 rue du Ruisseau 38290 SAINT QUENTIN-FALLAVIER – FRANCE Tél: +33 4 74 94 90 70 - Fax: +33 4 74 94 13 95 www.sectoriel.com / Email: sectoriel@sectoriel.fr	Pages	2/4
		Ref.	TDS9265M
		Rev.	04
		Date	09/2025

NORMALLY OPEN SOLENOID VALVE FOR GAS 6 BAR

AUTOMATIC – EVA-6 ND 15 TO 50

CONSTRUCTION

N°	Item
1	Solenoid stand
2	Solenoid
3	Shutter sealing
4	BSP ¼" pressure connection
5	Bottom
6	Cover fastening screw
7	Oring sealing
8	Body
9	Shutter
10	Cover
11	Power connector
12	Connector screw



Information given as an indication only, and subject to possible modifications



SECTORIEL S.A.
45 rue du Ruisseau
38290 SAINT QUENTIN-FALLAVIER – FRANCE
Tél: +33 4 74 94 90 70 - Fax: +33 4 74 94 13 95
www.sectoriel.com / Email: sectoriel@sectoriel.fr


Pages	3/4
Ref.	TDS9265M
Rev.	04
Date	09/2025

NORMALLY OPEN SOLENOID VALVE FOR GAS 6 BAR

AUTOMATIC – EVA-6 ND 15 TO 50


DIMENSIONS (mm)

Overall dimensions in mm			
BSP	A	B	C
1/2"	75	152	74
3/4"	75	152	74
1"	75	152	74
1"1/4"	160	250	140
1"1/2"	160	250	140
2"	160	250	140



PRESSURE DROP DIAGRAM

In mbar with P1 = 50 mbar



Information given as an indication only, and subject to possible modifications

	SECTORIEL S.A. 45 rue du Ruisseau 38290 SAINT QUENTIN-FALLAVIER – FRANCE Tél: +33 4 74 94 90 70 - Fax: +33 4 74 94 13 95 www.sectoriel.com / Email: sectoriel@sectoriel.fr	Pages	4/4
		Ref.	TDS9265M
		Rev.	04
		Date	09/2025