

**CONCENTRIC LUG BUTTERFLY VALVE INITIAL RANGE DUCTILE IRON BODY WITH STAINLESS
STEEL DISC AND EPDM ACS SEAT**

Lug butterfly valve initial range for drinking water.

Ductile iron EN GJS-400-15 body, stainless steel disc and EPDM ACS seat.

Between flanges PN10/PN16. 5 years warranty.

Handling possible with gearbox.

Thanks to the ISO 5211 plate, an actuator can be installed on the valve.



Certificate
3.1



Size : DN40 to DN300

Connection : Between flanges PN10/16

Min Temperature : -15°C

Max Temperature : +110°C (130°C temporarily)

Max Pressure : 16 Bars

Specifications : Long neck for isolation

Stainless steel disc

Vulcanised EPDM ACS seat

ISO 5211 mounting pad

Materials : Ductile iron EN GJS-400-15 body

the installation defects and wear defects are not covered by the guarantee

CONCENTRIC LUG BUTTERFLY VALVE INITIAL RANGE DUCTILE IRON BODY WITH STAINLESS STEEL DISC AND EPDM ACS SEAT

SPECIFICATIONS :

- Long neck for isolation
- ISO 5211 mounting pad
- Lug type
- Between flanges PN10 or PN16 from DN 40 to DN 300
- Full crossing stem
- 10 positions cranted lever, with locking device up to DN150
- Double PTFE gasket on stem
- Stainless steel disc
- Epoxy painting RAL5005 80 microns thickness
- Ductile iron EN GJS-400-15 (EN-JS1030)
- EPDM ACS vulcanised seat

USE :

- Cold and hot water, drinking water
- Min and max Temperature Ts : - 15°C to + 110°C (130°C temporarily)
- Max Pressure Ps : 16 bars
- Can be used at the end of the pipe (10 bars maxi) with a counter flange installed at the end of the valve

FLOW COEFFICIENT Kv (M3 / h) :

DN		40	50	65	80	100	125	150	200	250	300
Opening angle	10°	0,04	0,05	0,09	0,17	0,26	0,43	0,68	1,7	2,6	3,4
	20°	2	3	5	8	15	25	38	76	129	200
	30°	5	6	10	15	31	52	81	160	273	422
	40°	10	13	21	33	67	113	175	348	592	914
	50°	18	23	38	60	119	202	312	620	1055	1630
	60°	30	38	64	99	196	334	516	1025	1746	2697
	70°	48	60	102	156	310	529	817	1623	2764	4269
	80°	72	90	152	235	466	793	1226	2434	4145	6403
	90°	78	98	167	258	512	872	1347	2675	4555	7037


TORQUE VALUES (Nm, without safety coefficient) :

We recommend a safety coefficient of 30% minimum to determinate the actuator.

DN	40	50	65	80	100	125	150	200	250	300
PN10	9	12	19	25	38	58	85	159	253	369
PN16	10	13	21	26	42	65	95	175	277	536

CONCENTRIC LUG BUTTERFLY VALVE INITIAL RANGE DUCTILE IRON BODY WITH STAINLESS STEEL DISC AND EPDM ACS SEAT

PRESSURE / TEMPERATURE GRAPH (STEAM EXCLUDED) :



RANGE :

- Lug butterfly valve ACS with lever from DN32/40 to DN300 **Ref.1133A**



- Gearbox IP54 possible from DN32/40 to DN300 **Ref.1198001 to 1198006**




- Gearbox IP67 possible from DN32/40 to DN300 **Ref.1198301 to 1198306**



- Chain gearbox IP54 possible from DN32/40 to DN300 **Ref.1198201 to 1198206 (without chain)**
- Galvanized carbon steel chain for chain gearbox initial range **Ref.1198200 (per meter)**

**CONCENTRIC LUG BUTTERFLY VALVE INITIAL RANGE DUCTILE IRON BODY WITH STAINLESS
STEEL DISC AND EPDM ACS SEAT**


MATERIALS :



Item	Designation	Materials
1	Body	Ductile iron EN-JS1030 (EN GJS-400-15)
2	Disc	ASTM A351 CF8M
3	Seat	EPDM ACS
4	Stem	AISI 420
5	Bushing	PTFE
6	O ring	EPDM
7	Circlip	Steel
8	Circlip	Steel
	Lever	Aluminium

CONCENTRIC LUG BUTTERFLY VALVE INITIAL RANGE DUCTILE IRON BODY WITH STAINLESS STEEL DISC AND EPDM ACS SEAT


MATERIALS GEARBOX :



Item	Designation	Materials
1	Stem	Chromed steel
2	Pin	AISI 316
3	Indicator plate	Aluminium + NBR gasket
4	Indicator bolt, washer	AISI 316
5	Bolt, washer	AISI 316
6	Gear 1	Steel
7	Gear 2	Ductile iron EN GJS-400-15
8	O ring	NBR
9	Bonnet gasket	NBR
10	Internal set screw	Carbon steel
11	External set screw	AISI 316
12	Plastic cap	Plastic
13	Handwheel	Cast iron EN GJL-250 epoxy coating
14	Bonnet	Cast iron EN GJL-250 epoxy coating
15	Body	Cast iron EN GJL-250 epoxy coating
	Bolting to fix on valve	AISI 304

CONCENTRIC LUG BUTTERFLY VALVE INITIAL RANGE DUCTILE IRON BODY WITH STAINLESS STEEL DISC AND EPDM ACS SEAT


VALVES WITH LEVER SIZE (in mm) :



DN	40	50	65	80	100	125	150	200	250	300
A	61	77	88	95	107	122	144	171	205	235
B	130	137	142	158	180	192	215	242	280	310
Ø De	82	95	109	127	152	180	207	260	315	370
E	33	43	46	46	52	56	56	60	68	78
H	70	70	70	70	70	71	71	40	44	44
L	195	195	195	195	195	278	278	355	507	507
Ø P	65	65	65	65	65	90	90	125	150	150
Weig. (Kg)	2.43	3.13	3.73	4.98	5.64	9.06	10.96	16.67	31.4	42
Ref.	1133040A	1133050A	1133065A	1133080A	1133100A	1133125A	1133150A	1133200A-201A	1133250A-251A	1133300A-301A

CONCENTRIC LUG BUTTERFLY VALVE INITIAL RANGE DUCTILE IRON BODY WITH STAINLESS STEEL DISC AND EPDM ACS SEAT


VALVES WITH GEARBOX (in mm) :



DN	40	50	65	80	100	125	150	200	250	300
A	61	77	88	95	107	122	144	171	205	235
B	130	137	142	158	180	192	215	242	280	310
D	162							224		223
Ø De	82	95	109	127	152	180	207	260	315	370
E	33	43	46	46	52	56	56	60	68	78
H	112					162		191		192
H1	167	174	179	195	217	229	252	283	321	352
L1	44							66		77
Ø V	150					250		300		
Weig. (Kg)	5.68	6.28	6.76	8.49	9.86	12.59	14.49	23.66	36.42	51.6

CONCENTRIC LUG BUTTERFLY VALVE INITIAL RANGE DUCTILE IRON BODY WITH STAINLESS STEEL DISC AND EPDM ACS SEAT


SIZE GEARBOX (in mm) :



DN	32/80	100	125/150	200	250	300-350
C	9	11	14	17	22	27
Ø K	50	50	70	102	125	125
ISO	F05	F05	F07	F10	F12	F12
N x ØZ	4 x M6	4 x M6	4 x M8	4 x M10	4 x M12	4 x M12
L	37			41		42
D	162			224		223
L1	44			66		77
Ø D1	16			19		
Ø V	150		250	300		
Weight (kg)	3.51	4.22	3.53	6.99	7.42	9.6
Ref.	1198001	1198002	1198003	1198004	1198005	1198006

CONCENTRIC LUG BUTTERFLY VALVE INITIAL RANGE DUCTILE IRON BODY WITH STAINLESS STEEL DISC AND EPDM ACS SEAT


DISC AND NECK SIZE (in mm) :



DN	40	50	65	80	100	125	150	200	250	300
E1	37.7	47.06	59.81	75.56	98.37	117.02	147.65	195.3	242.5	292.6
E2	4.9	5	9.4	16.5	26.1	33.9	49.7	71.2	91.2	111.8
Ø E3 ±2	70	76	90	104	135	159	188	238	292	344
H6 ±2	76.7	79	79	87.5	92.3	90.3	99.2	99.5	103.8	105.8
Ø P	42.8	53	64.8	79.1	104.25	123.8	155.4	202.4	250.5	301.6
Ø T mini	43	53	65	79.5	104.5	124	155.5	202.5	250.5	302

**CONCENTRIC LUG BUTTERFLY VALVE INITIAL RANGE DUCTILE IRON BODY WITH STAINLESS
STEEL DISC AND EPDM ACS SEAT**


ISO 5211 MOUNTING PAD (in mm) :



DN	40	50	65	80	100	125	150	200	250	300
C	9	9	9	9	11	14	14	17	22	27
Ø K	50	50	50	50	50	70	70	102	125	125
ISO	F05	F05	F05	F05	F05	F07	F07	F10	F12	F12
Nx ØZ	4 x 7	4 x 7	4 x 7	4 x 7	4 x 7	4 x 9	4 x 9	4 x 11	4 x 13	4 x 13
H4	32	32	32	32	32	42	42	36	38	38
Ø P	65	65	65	65	65	90	90	125	150	150


**CONCENTRIC LUG BUTTERFLY VALVE INITIAL RANGE DUCTILE IRON BODY WITH STAINLESS
STEEL DISC AND EPDM ACS SEAT**

FLANGES LUG SIZE PN10/16 (in mm) :



DN	40	50	65	80	100	125	150
Ø K	110	125	145	160	180	210	240
Nb x ØL	4 x M16	4 x M16	4 x M16	8 x M16	8 x M16	8 x M16	8 x M20
Ref.	1133040A	1133050A	1133065A	1133080A	1133100A	1133125A	1133150A


FLANGES LUG SIZE PN10 (in mm) :



DN	200	250	300
Ø K	295	350	400
Nb x ØL	8 x M20	12 x M20	12 x M20
Ref.	1133200A	1133250A	1133300A

**CONCENTRIC LUG BUTTERFLY VALVE INITIAL RANGE DUCTILE IRON BODY WITH STAINLESS
STEEL DISC AND EPDM ACS SEAT**

FLANGES LUG SIZE PN16 (in mm) :



DN	200	250	300
Ø K	295	355	410
Nb x ØL	12 x M20	12 x M24	12 x M24
Ref.	1133201A	1133251A	1133301A

GEARBOX SPECIFICATIONS :

DN	32/80	100	125/150	200	250	300-350
Ref.	1198001	1198002	1198003	1198004	1198005	1198006
Ratio factor	24 :1	24 :1	24 :1	30 :1	30 :1	50 :1
Input torque (Nm)	18	18	18	58	58	60
Output torque (Nm)	170	170	170	700	700	1200

**CONCENTRIC LUG BUTTERFLY VALVE INITIAL RANGE DUCTILE IRON BODY WITH STAINLESS
STEEL DISC AND EPDM ACS SEAT**

STANDARDS :

- Manufacturer certified ISO 9001 : 2015 and ISO 14001 : 2015
- Designing according to API 609
- DIRECTIVE 2014/68/EU: For liquids of Group 2
 - Article 4, §3 (SEP), no CE marking
- Certificate 3.1 on request
- Pressure tests according to API 598, table 6
- Length according to ISO 5752 series 20, EN 558 series 20 (NF 29305)
- ISO 5211 mounting pad
- Between flanges according to EN 1092-1 PN10/16
- French drinking water agreement **A.C.S. N° 26 ACC LY 041**
- Valves according to LR Rules and Regulation for the classification of Ships, July 2025 (Type Approval Certificate) **Marine LLOYD'S REGISTER**. Marine and offshore subject to the valves complying LR Rules and Regulations for the particular services.
 - ISO 19921:2005
 - GB/T 22218 – 2008

ADVICE : Our opinion and our advice are not guaranteed and SFERACO shall not be liable for the consequences of damages.
The customer must check the right choice of the products with the real service conditions.