

780-781XS 3-WAYS BALL VALVES

FEATURES

The stainless steel 3-way 780XS (L-Port) and 781 XS (T-Port) steel and stainless steel ball valves provide the mixing, distribution or automatic discharge functions for pipes with non-loaded industrial fluids. It is a reduced-bore valve with an antistatic device. It is EC- and ATEX-approved. The ISO 5211 mounting pad allows the actuator to be directly assembled.

AVAILABLE MODELS

780 XS: L-Port / **781 XS:** T-Port

1.4408 stainless steel body.

1/4" to 2" diameters.



G thread connections



EMICO

LIMITS OF USE

Fluid pressure: PS	63 bar (20°C)
Fluid temperature: WT	- 40°C / +180°C



DIRECTIVES AND MANUFACTURING STANDARDS

OBJECT	Standard	ON	OBJECT	Standard
Pressure Equipment Directive 2014/68/EC	1/4" to 1": not subject		Final test	EN 12266
	1"1/4 to 2": category III	TÜV 0035	Material certificate	EN 10204
Size	EN 12516-1		Connection Motorisation	ISO 5211
Steel grades	EN 1503-1			
ATEX Directive	II 2G/D Tx zones 1,2,21 and 22	SIRA 0518		
	EN 13463-1 and 5			

Information given as an indication only, and subject to possible modifications




SECTORIEL S.A.
45 rue du Ruisseau
38290 SAINT QUENTIN-FALLAVIER – FRANCE
Telephone: +33 4 74 94 90 70 - Fax: +33 4 74 94 13 95
www.sectoriel.com / Email : sectoriel@sectoriel.fr

Pages	1/2
Ref.	TDS780XS
Rev.	02
Date	06/2026

780-781XS 3-WAYS BALL VALVES

CONSTRUCTION

No.	Name	Material	No.	Name	Material
1	Body	1.4408 SS	12	Lock washer	304 SS
2	Lateral ends	1.4408 SS	13	Lever nut	304 SS
3	Ball	1.4408 SS	14	Washer	304 SS
4	Seats	PTFE	15	Lever	304 SS
5	Stem	316 SS	16	Liner	PVC
6	Stem gasket	PTFE	17	Stop	304 SS
7	Body gaskets	PTFE	18	Nut	304 SS
8	Cable gland gasket	PTFE	19	O-ring	FKM
9	Washer	TFM 1600	20	Body gasket	PTFE
10	Spacer	304 SS	21	Central end	1.4408 SS
11	Belleville washer	304 SS	22	Spring	304 SS



DIMENSIONS (mm)

DN (G)	1/4"	3/8"	1/2"	3/4"	1"	1"1/4	1"1/2	2"
d	11	11	12.5	16	20	25	32	38
L	75.7	75.7	75.7	86.6	103	118.2	125.8	149
H	64.9	64.9	64.9	71.6	94.3	100	115.7	124.9
F	38.3	38.3	38.3	44.7	50.8	57.7	62.6	74.3
A	8.2	8.2	8.2	9.0	11.5	11.5	15.1	15.1
E	132	132	132	132	180	180	225	225
H1	36.8	36.8	36.8	44.1	55.1	60.7	75.2	84.4
D	9	9	9	9	11	11	14	14
ISO	F03/F04	F03/F04	F03/F04	F03/F04	F04/F05	F04/F05	F05/F07	F05/F07
Weight (kg)	0.33	0.33	0.33	0.5	0.9	1.7	2.2	3.8

Information given as an indication only, and subject to possible modifications

	SECTORIEL S.A. 45 rue du Ruisseau 38290 SAINT QUENTIN-FALLAVIER – FRANCE Telephone: +33 4 74 94 90 70 - Fax: +33 4 74 94 13 95 www.sectoriel.com / Email : sectoriel@sectoriel.fr		Pages	2/2
			Ref.	TDS780XS
			Rev.	02
			Date	06/2026