

**2 PIECES CARBON STEEL BALL VALVE PN16/40 FLANGED JC RANGE LONG PATTERN
(DIN 3202-1 F1) PTFE SEAT**

2 pieces split body ball valve JC with full bore for Chemical industries, petrochemical industries, hydraulic installation, heating, water distribution, compressed air.

Ball valve with firesafe certificate ISO 10497 and API 607 to reduce risks in case of fire.

Fugitive emission according to EN 15848-1 :2006 B Class and TA LUFT for an excellent tightness on the stem and to prevent external leakage.

PTFE seat for a temperature up to +230°C.

Compatible with explosive atmosphere, ATEX Zone 1&21 and Zone 2&22 thanks to the double antistatic device.

Handling possible with locking device, lockable gearbox, oval handwheel or stem extension.

Thanks to the ISO 5211 plate, an actuator can be installed on the valve.



Certificate
3.1

NACE
MR01-75



JC
VALVES



Size : DN15 to DN200
Connection : Flanged PN16/40 RF
Min Temperature : -29°C
Max Temperature : +230°C
Max Pressure : 40 Bars for PN40, 16 bars for PN16
Specifications : PTFE seat
ISO 5211 mounting pad
Anti blow-out stem, full bore
Fire safe ISO 10497 : 2004, API 607 5th, BS 6755 Part 2 and API 6FA

Materials : Carbon steel EN 1.0619

*the installation defects and wear defects are not covered by the guarantee

**2 PIECES CARBON STEEL BALL VALVE PN16/40 FLANGED JC RANGE LONG PATTERN
(DIN 3202-1 F1) PTFE SEAT**

SPECIFICATIONS :


- Full bore
- Anti blow-out stem
- PTFE seat
- Locking device on request
- ISO 5211 mounting pad
- 2 pieces type (Split body)
- PN40 Flanges R.F or PN16
- Antistatic device
- Fire safe ISO 10497 : 2004, API 607 5th, BS 6755 Part.2 and API 6FA
- Fugitive emissions EN 15848-1 : 2006 and TA LUFT VDI 2440
- Graphite packing + FKM O ring on stem
- With exhaust hole in the ball (located in the top of the ball to avoid overpressure in it)
- Blue painting RAL 5009 color, 15-50μ thickness

USE :

- Chemical industries, petrochemical industries, hydraulic installation, heating, water distribution, compressed air
- Min and max Temperature Ts : -29°C to + 230°C
- Max Pressure Ps : 40 bars for PN40 types, 16 bars for PN16 types (see graph)
- Vacuum 10⁻² torr
- Compressed air (ambient temperature) : 40 bars maximum for PN40 types, 16 bars for PN16 types
- Steam : 12 bars maximum

PRESSURE / TEMPERATURE GRAPH (STEAM EXCLUDED) :

Pressure (Bar)



2 PIECES CARBON STEEL BALL VALVE PN16/40 FLANGED JC RANGE LONG PATTERN (DIN 3202-1 F1) PTFE SEAT

FLOW COEFFICIENT Kvs (in m³ / h) :

DN	15	20	25	32	40	50	65	80	100	125	150	200
Kvs (m ³ / h)	20	40	75	130	170	270	550	1000	1650	3000	4200	9000

TORQUES VALUES (in Nm without safety coefficient) :

DN	BTO*	RTO	ETO	BTC	RTC	ETC*	MAST Stem A479 F316	MAST Stem A182 F51	Ps (bars)
15	11	6	7	8	6	9	26	57	40
20	14	7	8	11	7	11	26	57	40
25	20	10	12	15	10	16	26	57	40
32	25	13	15	19	13	20	69	151	40
40	33	17	20	25	17	26	85	185	40
50	46	23	28	35	23	37	85	185	40
65	61	31	37	46	31	49	176	386	16
	66	33	40	50	33	53	176	386	40
80	97	49	58	73	49	78	246	539	16
	116	58	70	87	58	93	246	539	40
100	133	67	80	100	67	106	305	668	16
	171	86	103	128	86	137	305	668	40
125	226	113	136	170	113	181	607	1329	16
	283	142	170	212	142	226	607	1329	40
150	320	160	192	240	160	256	974	2131	16
	463	232	278	347	232	370	974	2131	40
200	694	347	416	521	347	555	1387	3034	16
	1020	510	612	765	510	816	1387	3034	40

BTO* : Break to open

ETC* : End Torque Close

RANGE :

- Carbon steel body ball valve with handle flanged PN40 **Ref. 340AIT** from DN 15 to DN 150
- Carbon steel body ball valve with handle flanged PN16 **Ref. 316AIT** from DN 65 to DN 150
- Carbon steel body ball valve with free stem PN16 **Ref. 316AIT** DN200 or PN40 **Ref.340AIT** DN200

CONNECTION :

- PN40 Flanges R.F. for Ref.340AIT and PN16 for Ref.316AIT

 Sferaco 90 rue du Ruisseau 38297 St Quentin Fallavier Tel: + 33 (0) 474.94.15.90 Fax: + 33 (0) 474.95.62.08 Internet: www.sferaco.com E-mail: info@sferaco.fr

Date : 12/25

Rev.06

**2 PIECES CARBON STEEL BALL VALVE PN16/40 FLANGED JC RANGE LONG PATTERN
(DIN 3202-1 F1) PTFE SEAT**

ACCESSORIES :



- Reinforced locking device

DN	15	20	25	32	40	50	65	80	100	125	150	200
Ref.	9830120	9830121	9830122	9830123	9830124	9830125	9830126	9830127	9830128	9830129		

- Stainless steel handle

DN	15	20	25	32	40	50	65	80	100	125	150
Ref.	9830513	9830514	9830515	9830516	9830517	9830518	9830519	9830520			

- Stainless steel oval handwheel

DN	15	20	25	32	40	50
Ref.	9830575	9830578	9830576	9830577		

- Lockable gearbox

DN	125	150	200
Ref.316	9830598	9830592	9830593
Ref.340			983595

- Single stainless steel stem extension 100 mm (can't be used with oval handwheel)


DN	15	20	25	32	40	50	65	80	100	125	150
Ref. JC	9810615	9810616	9810617	9810618	9810619	9810620	9810621	9810622			

- Stainless steel stem extension 100 mm with ISO plate

DN	15	20	25	32	40	50	65	80	100	125	150	200
Ref. SF	JCRISO015020	JCRISO025	JCRISO032	JCRISO040050	JCRISO065	JCRISO080	JCRISO100	JCVSSBI125	JCVSSBI150	JCVSSBI200		

**2 PIECES CARBON STEEL BALL VALVE PN16/40 FLANGED JC RANGE LONG PATTERN
(DIN 3202-1 F1) PTFE SEAT**

VALVE MATERIALS :



Repairability :



* Gaskets kit (Items 5,11, 12, 13, 18, 46 and 72)		
DN	Ref.PN16	Ref. PN40
DN15	9804600	
DN20	9804601	
DN25	9804602	
DN32	9804603	
DN40	9804604	
DN50	9804605	
DN65	9804606	
DN80	9804607	
DN100	9804608	9804708
DN125	9804609	
DN150	9804610	9804710
DN200	9804611	-

(* : Included in gaskets kit)


Item	Designation	Materials
1	Body	EN 1.0619
2	Ends	
3	Ball DN15-25	ASTM A479 Tp.316
	Ball DN 32-200	Inox ASTM A 351 CF8M
4	Stem	ASTM A479 Tp.316 or Duplex ASTM A182 F51
5*	Seat	PTFE
6	Handle	Carbon steel A216 WCB
7	Packing nut	Steel
8	Elastic ring	Steel
9	Stop washer	Steel
10	Packing gland	AISI 303
11*	Packing	Graphite
12*	Gasket	PTFE filled with 25% glass

Item	Designation	Materials
13*	Body spiral seat	AISI 316L + PTFE + Graphite
14	Pin	Steel
15	Screw (stud DN32-100)	DIN 933 8.8 zinc dichrom.
16	Handle screw	DIN 933 A4-70
17	Washer	Zinc plated carbon steel
18*	Thrust washer	PTFE filled with 25% glass
19	Antistatic device	Stainless steel
28	Nut (DN32-100)	DIN 934 8.8 zinc dichrom.
39	Stem bushing (DN25-200)	PTFE filled with 25% glass
41	Spacer (DN40-200)	Steel
46*	Washer	AISI 304
72*	O ring	FKM
89	ID plate	Stainless steel

Sferaco 90 rue du Ruisseau 38297 St Quentin Fallavier Tel: + 33 (0) 474.94.15.90 Fax: + 33 (0) 474.95.62.08 Internet: www.sferaco.com E-mail : info@sferaco.fr

**2 PIECES CARBON STEEL BALL VALVE PN16/40 FLANGED JC RANGE LONG PATTERN
(DIN 3202-1 F1) PTFE SEAT**


LOCKABLE GEARBOX MATERIALS :



Item	Designation	Materials
1	Handwheel	Carbon steel
2	Screw	
3	Stem key	
4	Input shaft	AISI 1045
5	Oil seal	Rubber
6	Bearing	Cu Base Alloy
7	Oil bearing	
8	Thrust bearing	Carbon steel
9	Worm	AISI 1045
10	Pin	Carbon steel
11	Plug	
12	Screw	Cast iron
13	Indicator plate	
14	Screw	Carbon steel
15	Cover	
16	Housing	Rubber
17	O ring	
18	Worm gear	Ductile iron
19	Nut	Carbon steel
20	Stop screw	
21	Nut	
22	Washer	
23	Locking device	

**2 PIECES CARBON STEEL BALL VALVE PN16/40 FLANGED JC RANGE LONG PATTERN
(DIN 3202-1 F1) PTFE SEAT**


VALVES SIZE DN15-50 (in mm) :



PN	PN40					
DN	15	20	25	32	40	50
Ø P	15	20	25	32	40	50
L	130	150	160	180	200	230
L1	53	52	48.5	54	55	61
E	164	164	164	210	213	213
H	111	118	130	131	148	155
H1	-	-	-	-	-	-
H2	46	53	58	66.5	76	83.5
Weight (in Kg)	3	3.8	5.2	7.6	9.6	12.9
Ref.	340AIT015	340AIT020	340AIT025	340AIT032	340AIT040	340AIT050

**2 PIECES CARBON STEEL BALL VALVE PN16/40 FLANGED JC RANGE LONG PATTERN
(DIN 3202-1 F1) PTFE SEAT**

VALVES SIZE DN65-200 (in mm) :




PN	PN16					
DN	65	80	100	125	150	200*
Ø P	65	80	100	125	151	203
L	290	310	350	400	480	600
L1	75.5	82	90.5	120	135	200
E	348	445	495	698	698	868
H	169	207	232	265	298	353
H1	-	-	118	138	160	208
H2	97	111	133	156	183	233
Weight (in Kg)	18.3	24	36	58	81	111
Ref.	316AIT 065	316AIT 080	316AIT 100	316AIT 125	316AIT 150	316AIT 200

PN	PN40				
DN	65	80	100	125	150
Ø P	65	80	100	125	151
L	290	310	350	400	480
L1	75.5	74.5	91	120	135
E	348	445	495	698	698
H	169	207	232	265	298
H1	-	-	118	138	160
H2	97	111	133	156	183
Weight (Kg)	18.5	25	39	63	87
Ref.	340AIT 065	340AIT 080	340AIT 100	340AIT 125	340AIT 150

* Handle on request for DN200 (free stem as standard)

**2 PIECES CARBON STEEL BALL VALVE PN16/40 FLANGED JC RANGE LONG PATTERN
(DIN 3202-1 F1) PTFE SEAT**


ISO MOUNTING PAD AND STEM SIZE (in mm) :




PN	PN16/40											
DN	15	20	25	32	40	50	65	80	100	125	150	200
H3	1.5				3							4
H4	11.2	14.7	22.7	32	41.5	41.5	44	44.5	56.5	56	68	72
H5	5	8.5	9.5	13	18.3	18.3	18.6	18.6	27.8	24.7	37.1	36.5
C	9	9	9	12	13	13	16	18	20	25	29	32
Ø Y	M12x1.5			M16x1.5	M18x1.5		M22x1.5	M25x1.5	M28x1.5	M35x2	M40x2	M45x2
Ø D	35				55			70		85		100
Ø K	50	50	50	50	70	70	70	102	102	125	125	140
ISO	F05	F05	F05	F05	F07	F07	F07	F10	F10	F12	F12	F14
N x Ø Z	4 x M6	4 x M6	4 x M6	4 x M6	4 x M8	4 x M8	4 x M8	4 x M10	4 x M10	4 x M12	4 x M12	4 x M16

**2 PIECES CARBON STEEL BALL VALVE PN16/40 FLANGED JC RANGE LONG PATTERN
(DIN 3202-1 F1) PTFE SEAT**

LOCKABLE GEARBOX SIZE DN125-200 (in mm) :




COUPLING :



PN	PN16/40		PN16	PN40
DN	125	150	200	
H	102			105
H1	80	90		
H2	56			50
H3	365			480
H4	255			345
L	217			242
L1	77.5			90
L2	156			
Ø V	465			600
ISO	F14			
ISO1	F12		F14	
C	25	29	32	
D	114	130		127
Ø E	45			65
Weight (in Kg)	21.7	22.4	22.8	28.5
Torque (Nm)	1200			
Ref.	9830598	9830592	9830593	9830595


**2 PIECES CARBON STEEL BALL VALVE PN16/40 FLANGED JC RANGE LONG PATTERN
(DIN 3202-1 F1) PTFE SEAT**

OVAL HANDWHEEL SIZE DN15-50 (in mm) :



DN	15	20	25	32	40	50
A	160	160	160	200	216	216
B	54	54	54	56	57	57
C	75	75	75	90	100	100
Weight (Kg)	0.25	0.25	0.25	0.5	0.55	0.55
Ref.	9830575	9830578		9830576	9830577	


STAINLESS STEEL HANDLE SIZE DN15-200 (in mm) :



DN	15	20	25	32	40	50	65	80	100	125	150	200
A	163.5			300	212.5		347.5	445	495	697.5		867.5
B	58.5			45	48.5		46.5	70	70	77.5	84.5	84.5
C	12			16	21		20		29	30	40	
D	18.5			22	25.5			33		47		55
Weight (Kg)	0.2			0.3	0.53		0.63	1.52	1.85	2.95	3.4	4.6
Ref.	9830513			9830514	9830515		9830516	9830517	9830518	9830519	9830520	

**2 PIECES CARBON STEEL BALL VALVE PN16/40 FLANGED JC RANGE LONG PATTERN
(DIN 3202-1 F1) PTFE SEAT**

FLANGES SIZE (in mm) :



PN	PN40						PN16					
DN	15	20	25	32	40	50	65	80	100	125	150	200
Ø C	45	58	68	78	88	102	122	138	158	188	212	268
Ø D	95	105	115	140	150	165	185	200	220	250	285	340
Ø K	65	75	85	100	110	125	145	160	180	210	240	295
Nb x Ø L	4 x 14	4 x 14	4 x 14	4 x 18	4 x 18	4 x 18	4 x 18	8 x 18	8 x 18	8 x 18	8 x 22	12 x 22
b	16	18	18	18	18	20	18	20	20	22	22	24
e	2	2	2	2	3	3	3	3	3	3	3	3

PN	PN40					
DN	65	80	100	125	150	200
Ø C	122	138	162	188	218	285
Ø D	185	200	235	270	300	375
Ø K	145	160	190	220	250	320
Nb x Ø L	8 x 18	8 x 18	8 x 22	8 x 26	8 x 26	12 x 30
b	22	24	24	26	28	37
e	3	3	3	3	3	3

2 PIECES CARBON STEEL BALL VALVE PN16/40 FLANGED JC RANGE LONG PATTERN (DIN 3202-1 F1) PTFE SEAT

STANDARDS :

- Manufacturer certified ISO 9001:2015 and ISO 14001 : 2015
- DIRECTIVE 2014/68/EU: For liquids or Gas of Group 1
 - DN15-25: Article 4, §3 (SEP), no CE marking
 - DN32: Risk category I, CE marking
 - DN40-50: Risk category II, CE 0056 marking
 - PN16 Types:
 - DN65-80: Risk category I, CE marking
 - DN100-200 : Risk category II, CE0056 marking
 - PN40 Types:
 - DN65-100: Risk category II, CE 0056 marking
 - DN125-200: Risk category III, CE 0056 marking
- Certificate 3.1 on request
- Valve designing according to EN 1983 – ISO 17292 and EN 12516
- Materials according to NACE MR 01-75
- Pressure Tests according to EN 12266-1, Rate A
- Marking according to EN 19
- Fire safe according to ISO 10497 : 2004, API 607 5th, BS6755 Part 2, and API 6FA 1994
- Fugitive Emissions according to EN 15848-1 : 2006 B Class and TA LUFT VDI 2440
- SIL2 according to IEC/EN 61508, SIL 3 possible according to the type of installation
- Flanges R.F. type B1 according to EN 1092-1 PN16/40
- Shell finishing quality : MSS SP 55
- ISO 5211 mounting pad
- Length according to EN 558 series 1 (long pattern DIN 3202-1 F1)
- ATEX Group II Category 2 G/2Dc Zone 1 & 21 Zone 2 & 22 (optional marking) up to DN200 according to directive 2014/34/EU
- Russian certificate TRCU 10, TRCU 12 and TRCU 32 (EAC marking and declaration **on request**)
- Valves according to EN 14432-2024 Tank equipment for the transport of dangerous goods

ADVICE : Our opinion and our advice are not guaranteed and SFERACO shall not be liable for the consequences of damages.
The customer must check the right choice of the products with the real service conditions.